

## SAFETY INFORMATION SHEET

# POLYPROPYLENE HD915CF

#### 1. IDENTIFICATION

Product name: HD915CF

Intended use: Raw material for plastic industry

Manufacturer: Abu Dhabi Polymers Co. Ltd (Borouge)

Address: P.O. Box 11764, Ruwais, U.A.E.

Telephone: +9712 6020600 Facsimile: +9712 6020771

Supplier: Borouge Pte Ltd

Address: 1 George Street, #18-01, Singapore 049145

Telephone: +65 6275 4100 Facsimile: +65 6377 1233 Email: info@borouge.com

#### 2. HAZARDS IDENTIFICATION

### **GHS** classification:

Physical: No classification. Health: No classification. Environmental: No classification.

Other hazards: The product burns, but is not classified as flammable

Inhalation of dust may irritate the respiratory tract.

Prolonged inhalation of high doses of decomposition products may give headache

or irritation of the respiratory tract.

Dust from the product (when mixed with air in critical proportions and in the presence of an ignition source) may present a dust explosion hazard.

Spilled material may present a slipping hazard.

## **GHS label elements:**

Pictograms: Nil.
Signal word: Nil.
Hazard Statements: Nil.
Precautionary statements: Nil.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

The product is a polypropylene polymer.

Contains no substance classified as hazardous in concentrations, which should be taken into account according to Singapore Standard SS 586: Part 2: 2014 (Globally Harmonized System of classification and labeling of chemicals – Singapore adaptations).

Borouge Pte Ltd 1 George Street, #18-01 Singapore 049145 T +65 6275 4100 F +65 6377 1233





#### 4. FIRST AID MEASURES

Inhalation: If experiencing respiratory symptoms: Remove victim to fresh air and keep at rest

in a position comfortable for breathing. Get medical advice / attention.

If molten material comes in contact with skin, cool with plenty of water. Do not Skin contact:

remove solidified product.

Eve contact: No specific instruction needed. No specific instruction needed. Ingestion:

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water in spread jet, dry chemicals, foam or Carbon Dioxide.

Specific hazards during fire-fighting: Product will burn under fire conditions. Dust from the product

(when mixed with air in critical proportions and in the presence of an ignition source) may present a dust explosion hazard. Principal

toxicant in the smoke is Carbon Monoxide.

Special protective actions for Fire fighters should wear self-contained breathing apparatus,

boots,

fire-fighters: gloves, goggles and full protective clothing. Extinguish from the

> upwind direction.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective NO flames. NO sparks. Eliminate all sources of ignition.

equipment and emergency measures: Avoid breathing dust. Use personal protective equipment as

required.

Refer to Section 8: Exposure Controls / Personal Protection.

Suck or sweep up spill. All spill of material must be removed

Methods for cleaning up:

immediately

to prevent slipping accidents. Prevent product from entering

environment

and drains

### 7. HANDLING AND STORAGE

Handling: During processing and thermal treatment of the product, small amounts of volatile

hydrocarbons may be released. Provide adequate ventilation. Local exhaust ventilation may be necessary. Avoid inhalation of dust and decomposition fumes. Dust from the product gives a potential risk for dust explosion. Avoid the formation or spread of dust in the atmosphere. Avoid the build-up of dust. Clean regularly. Ground container and receiving

equipment. Take precautionary measures against static discharge

Storage: Safety aspects do not require any special precautions in terms of storage. Keep in a dry

place. More information on storage can be found in Product Data Sheet (PDS) for this

product.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component	Basis	Control parameters / Occupational exposure limits	
Inhalable dust	USA / ACGIH	TLV-TWA: 10 mg/m <sup>3</sup>	

Borouge Pte Ltd 1 George Street, #18-01 Singapore 049145 T +65 6275 4100 F +65 6377 1233





	UK HSE EH40/2005	8 hr TWA:	10 mg/m <sup>3</sup>
Respirable dust	USA / ACGIH	TLV-TWA:	3 mg/m <sup>3</sup>
	UK HSE EH40/2005	8 hr TWA:	4 mg/m <sup>3</sup>

Engineering controls: Extraction to remove dust at its source. Provide adequate ventilation.

Local exhaust ventilation may be necessary.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Solid, pellet, natural colour Melting point / range: 130-170°C Odour: Odourless Ignition temperature: >320°C

Density: 0.9-1.0g/cm<sup>3</sup> Solubility in water: Insoluble in water

#### 10. STABILITY AND REACTIVITY

Chemical stability: The product is a stable thermoplastic.

Reactivity: No chemical reactivity

Conditions to avoid: Dusty conditions, heat, open flame, spark, static electricity.

Incompatible materials: Nil.

Hazardous decomposition materials: On combustion releases: Oxides of Carbon.

#### 11. TOXICOLOGICAL INFORMATION

The product is not classified as a hazardous mixture according to Singapore Standard SS 586: Part 2: 2014 (Globally Harmonized System of classification and labeling of chemicals – Singapore adaptations). However, inhalation of dust may irritate the respiratory tract. Prolonged inhalation of high doses of decomposition products may give headache or irritation of the respiratory tract.

## 12. ECOLOGICAL INFORMATION

The product is not classified as hazardous to the environment according to Singapore Standard SS 586: Part 2: 2014 (Globally Harmonized System of classification and labeling of chemicals – Singapore adaptations).

#### 13. DISPOSAL CONSIDERATIONS

Reuse or recycle if not contaminated. The product may be safely used as fuel. Proper combustion does not require any special flue gas control. Check with local regulations.

#### 14. TRANSPORT INFORMATION

Land (RID / ADR): Not regulated.
Sea (IMO / IMDG): Not regulated.
Air (ICAO-IATA): Not regulated.







#### 15. REGULATORY INFORMATION

Chemical inventory	Status
Australia / AIIC	Υ
Canada / DSL:	Υ
China / IECSC:	Υ
Europe / EINECS or ELINCS or NLP:	Р
Japan / ENCS:	Υ
Korea / KECI:	Υ
New Zealand / NZIoC:	Е
Philippines / PICCS:	Υ
Taiwan / TCSI:	Υ
USA / TSCA (all relevant	
ingredients designated as active):	Υ

Y = All ingredients are on the inventory.

E = All ingredients are on the inventory or exempt from listing.

P = One or more ingredients fall under the polymer exemption or are on the no longer polymer list. All other ingredients are on the inventory or exempt from listing.

N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing.

# **16. OTHER INFORMATION**

Reasons for revision: Changes and / or additions made to Sections 2, 7,15 and 16.

Prepared by: Product Stewardship Specialist.

Date prepared: 19/07/2020 Document No.: CHSE-SIS-057

Rev. No.: 6

## 17. STANDARDS

Borouge is certified to various ISO standards, please refer to Borouge.com for more information.

For more information:

Website: <a href="mailto:www.borouge.com">www.borouge.com</a> I Email: <a href="mailto:product.stewardship@borouge.com">product.stewardship@borouge.com</a>

## **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication, however, we do not assume any liability whatsoever for the accuracy and completeness of such information.

Borouge makes no warranties which extend beyond the description contained herein. Nothing herein shall constitute any warranty of merchantability or fitness for a particular purpose.

It is the customer's responsibility to inspect and test our products in order to satisfy itself as to the suitability of the products for the customer's particular purpose. The customer is responsible for the appropriate, safe and legal use, processing and handling of our products.

No liability can be accepted in respect of the use of Borouge's products in conjunction with other materials. The information contained herein relates exclusively to our products when not used in conjunction with any third party materials.

Borouge Pte Ltd 1 George Street, #18-01 Singapore 049145 T +65 6275 4100 F +65 6377 1233

